

SDS reference: SDS-097A-CLP

Safety Data Sheet ALbee[™] Flame O₂

ð DANGER 2.2: Non flammable, 5.1: Oxidising non toxic gas. substances.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name SDS No. Chemical description CAS No. EC No. EC index No. Registration-No. Chemical formula

Relevant identified uses

- : ALbee[™] Flame O₂. : SDS-097A-CLP. : Oxygen. : 7782-44-7. : 231-956-9. : 008-001-00-8. : Listed in Annex IV / V REACH, exempted from registration. : O₂. 1.2. Relevant identified uses of the substance or mixture and uses advised against : Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas. Welding, cutting, heating and brazing.
 - Laboratory use. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Water treatment. Laser gas. Contact supplier for more information on uses.

1.3. Details of the supplier of the safety data sheet

Company identification

: Air Liquide UK Ltd. Station Road, Coleshill, B46 1JY Birmingham United Kingdom. 01675 462424. genenq.aluk@airliquide.com

1.4. Emergency telephone number

Emergency telephone number

2.3. Other hazards

Hazards identification SECTION 2:

2.1. Classification of the substance or mix Classification according to Regulation (EC) No. 1272 Physical hazards Gases under pressure		H270. H280.
2.2. Label elements Labelling according to Regulation (EC) No. 1272/200	08 [CLP]	
Hazard pictograms (CLP)	GHS03 GHS04	
Signal word (CLP)	: Danger.	
Hazard statements (CLP)	: H270 - May cause or intensify fire; oxi H280 - Contains gas under pressure;	
Precautionary statements (CLP)		
- Response	 P244 - Keep valves and fittings free fr - Keep away from clothing and other of P370+P376 - In case of fire: stop leak P403 - Store in a well-ventilated place P410+P403 - Protect from sunlight. S 	combustible materials. if safe to do so. e.

: 01675 462695.



SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oxygen	(CAS No) 7782-44-7 (EC no) 231-956-9 (EC index no) 008-001-00-8 (Registration-No.) *1	100	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixture

: Not applicable.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Skin contact Eye contact Ingestion

- : Remove victim to uncontaminated area.
- : Adverse effects not expected from this product.
- : Adverse effects not expected from this product.
- : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Firefighting measures	
5.1. Extinguishing media Suitable extinguishing media Unsuitable extinguishing media	Water spray or fog.Do not use water jet to extinguish.
5.2. Special hazards arising from the subscription between the subscription between the subscription products	 stance or mixture Exposure to fire may cause containers to rupture/explode. Supports combustion. None.
5.3. Advice for firefighters Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	 Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	: Try to stop release.
	Evacuate area.
	Monitor concentration of released product.
	Eliminate ignition sources.
	Ensure adequate air ventilation.
	Prevent from entering sewers, basements and workpits, or any place where its accumulation can
	be dangerous.
	Act in accordance with local emergency plan.
	Stay upwind.
6.2. Environmental precautions	
·	: Try to stop release.
6.3. Methods and material for containme	nt and cleaning up
	: Ventilate area.
6.4. Reference to other sections	

: See also sections 8 and 13.

7.1. Precautions for safe handling	
Safe use of the product	 Do not breathe gas. Avoid release of product into atmosphere. The substance must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consult supplier for specific recommendations. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use no oil or grease. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Use only oxygen approved lubricants and oxygen approved sealings.
Safe handling of the gas receptacle	 Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, includir	 Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over.
7.3. Specific end use(s)	Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Segregate from flammable gases and other flammable materials in store. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

: None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

8.2.1. Appropriate engineering controls

8.2.1. Appropriate engineering controls	
	 Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.g.	personal protective equipment
Eye/face protection	 A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection.
Skin protection	
Hand protection	 Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. Consider the use of flame resistant safety clothing. Standard EN ISO 14116 - Limited flame spread materials. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

SECTION 8: Exposure controls/personal protection (cont)

Respiratory protection Thermal hazards None necessary.None necessary.

8.2.3. Environmental exposure controls

: None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	-Da Cara
Physical state at 20°C / 101.3k	
	our : Colourless.
Odour	: No odour warning properties.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
рН	: Not applicable.
Melting point / Freezing point	: -219°C.
Boiling point	: -183°C.
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	
Explosive limits	: Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Relative density, liquid (water=1)	: 1.1.
Relative density, gas (air=1)	: 1.1.
Water solubility	: 39 ma/l.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic gases.
Auto-ignition temperature	: Not applicable.
Viscosity	: Not applicable.
Explosive properties	: Not applicable.
Oxidising properties	: Oxidiser.
9.2. Other information	
Molar mass	: 32 g/mol.
Critical temperature [°C]	: -118°C.
Coefficient of oxygen equivalency (Ci)	: 1.

Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
SECTION 10: Stability and reactivity	
10.1. Reactivity	: No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	: Stable under normal conditions.
10.3. Possibility of hazardous reactions	: Violently oxidises organic material.
10.4. Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
10.5. Incompatible materials	 May react violently with reducing agents. May react violently with combustible materials. Keep equipment free from oil and grease.

high pressure (> 30 bar) oxygen lines in case of combustion. For additional information on compatibility refer to ISO 11114.

Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in

10.6. Hazardous decomposition products

: None.

111. Information on toxicological effects Acute toxicity Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Toxic for reproduction : Fertility Toxic for reproduction : unborn child STOT-single exposure STOT-repeated exposure Aspiration hazard	 No known toxicological effects from this product. No known effects from this product.
SECTION 12: Ecological information	
12.1. Toxicity Assessment EC50 48h - Daphnia magna [mg/l] EC50 72h - Algae [mg/l] LC50 96 h - Fish [mg/l]	 No ecological damage caused by this product. No data available. No data available. No data available.
12.2. Persistence and degradability Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential Assessment	: No ecological damage caused by this product.
12.4. Mobility in soil Assessment	: No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessme Assessment	ent : Not classified as PBT or vPvB.
12.6. Other adverse effects Effect on ozone layer Effect on the global warming	: None. : None.
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on suitable disposal methods.
Commission Decision 2001/118/EC)	: 16 05 04: Gases in pressure containers (including halons) containing dangerous substances.
13.2. Additional information	: None.
SECTION 14: Transport information	
14.1. UN number UN-No.	: 1072.
14.2. UN proper shipping name Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)	: Oxygen, compressed.: Oxygen, compressed.: Oxygen, compressed.
14.3. Transport hazard class(es) Labelling	
	2.2 : Non-flammable, non-toxic gases. 5.1 : Oxidizing substances.
Transport by road/rail (ADR/RID) Class Classification code	: 2. : 10.

Classification code Hazard identification number **Tunnel Restriction** Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s)) Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) Emergency Schedule (EmS) - Fire Emergency Schedule (EmS) - Spillage

- : 25.
- : E Passage forbidden through tunnels of category E.
- : 2.2 (5.1).
- : 2.2 (5.1).
- : F-C.
- : S-W.

SECTION 14: Transport information (cor	nt)
14.4. Packing group Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)	Not applicable.Not applicable.Not applicable.
14.5. Environmental hazards Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)	: None. : None. : None.
14.6. Special precautions for user Packing Instruction(s) Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only	
Transport by sea (IMDG) Special transport precautions	 P200. Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure there is adequate ventilation. Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

: Not applicable.

SECTION 15: Regulatory information	
EU-Regulations	ulations/legislation specific for the substance or mixture
Restrictions on use	: None.
Seveso directive 96/82/EC	: Listed.
National regulations National legislation Kenn-Nr.	Ensure all national/local regulations are observed.743.
15.2. Chemical safety assessment	
	: A CSA does not need to be carried out for this product.
SECTION 16: Other information	

Indication of changes Training advice Further information	 Revised safety data sheet in accordance with commission regulation (EU) No 453/2010. Ensure operators understand the hazard of oxygen enrichment. This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
DISCLAIMER OF LIABILITY	 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.



