

# Samsung WindFree™ Avant

The Samsung WindFree™ range keeps you comfortably cool without any cold drafts. It provides intelligent indoor climate comfort thanks to smart controls that adapt to your personal preferences, automatically maintaining optimal conditions.

### WindFree™ Cooling

WindFree™ technology enhances your indoor comfort by using thousands of micro-holes to disperse fresh air uniformly without any unpleasant blasts of cold wind. In WindFree™ mode, air is spread softly and silently, creating a 'Still Air' environment' that provides you total well-being day and night.

### **Smart Operation**

Al Auto Comfort<sup>2</sup> introduces you to an intelligent way of living. It analyses your room conditions and usage patterns<sup>3</sup>, and then automatically adjusts the temperature. Temperatures can also be managed remotely using the SmartThings App<sup>4</sup>. Turning it on and off, selecting the cooling mode or scheduling its operation is just one touch away.

#### WiFi Control

Temperatures in your building can be managed remotely using the SmartThings App<sup>5</sup>. Turning it on and off, selecting the cooling mode, scheduling its operation or monitoring the power consumption is just one touch away. The Bixby 2.0 Artificial Intelligence (AI) system<sup>6</sup> analyses and predicts your needs so it can suggest the best settings for inside your home.

## Samsung WindFree™ Avant

- Three-step cooling: Fast Cooling mode, Dehumidification mode and WindFree™ Cooling mode.
- Tri-Care Filter system with Zeolite Coating.
- Al Auto Comfort.
- Wi-Fi Control with Samsung SmartThings and Bixby voice controls.
- Compressor with Digital Inverter Boost technology.
- Triple Protector Plus to protect compressor, fin and controller from power surges.
- Auto Clean Functionality.







## **Specifications**

Model No.	Indoor Unit		AR09TXEAAWKNEU	AR12TXEAAWKNEU	AR18TXEAAWKNEU	AR24TXEAAWKNEU
	Outdoor Unit (1-phase)		AR09TXEAAWKXEU	AR12TXEAAWKXEU	AR18TXEAAWKXEU	AR24TXEAAWKXEU
Capacity	Cooling	kW	2.50(0.96-3.35)	3.50(0.99-4.00)	5.0(1.60-6.70)	6.50(1.40-7.60)
	Heating		3.2 (0.72-5.0)	4.0(0.74-5.50)	6.0(1.30-8.00)	7.40(1.20-9.70)
JK Capacity	Sensible cooling	kW	2.39	2.92	4.33	5.40
Efficiency	EER	W/W	4.39	3.76	3.60	3.33
	COP1		4.21	3.74	3.53	3.15
	SEER1	W/W	7.9/ A++	7.3/ A++	6.8/ A++	6.4/ A++
	SCOP <sup>1</sup>		4.6/ A++	4.6/ A++	4.1/ A+	4.0/ A+
Annual Energy Consumption	Cooling	kWh/a	111	168	257	355
	Heating		670	730	1,298	1,435
Sound Pressure	Indoor (H/Silent)	dB(A)	38/16	40/16	41/25	45/27
	Outdoor (Cooling only)		45	46	51	54
Sound Power	Indoor Unit	dB(A)	54	57	58	62
	Outdoor Unit		59	62	65	68
Airflow Rate	Indoor Cooling (T/H/M/L)	l/s	158/150/142/123	175/167/150/132	262/242/220/188	293/262/232/188
	Heating (T/H/M/L)	l/s	185/175/167/150	202/193/175/158	262/242/220/188	305/273/242/200
	Outdoor	l/s	750	750	833	833
Dimensions (W x H x D)	Indoor		889 x 299 x 215	889 x 299 x 215	1,055 x 299 x 215	1,055 x 299 x 215
	Outdoor	— mm –	790 x 548 x 285	790 x 548 x 285	880 x 638 x 310	880 x 638 x 310
Net Weight	Indoor Unit	- kg	9.9	9.9	12.2	12.5
	Outdoor Unit		32.1	32.1	42.7	43.7
Refrigerant	Pipe Size Gas	ø, inch	3/8	3/8	1/2	5/8
	Liquid		1/4	1/4	1/4	1/4
	Std/Max Pipe Length (Height)	_ m _	3/15(8)	3/15(8)	3/30(15)	3/30(15)
	Pre Charge to		5	5	5	5
	Factory Charging	kg	0.94	0.94	1.3	1.3
	Additional Charge	g/m	15	15	15	15
	CO <sub>2</sub> Equivalent (R32 - GWP 675)	tCO <sub>2</sub> e	0.63	0.63	0.88	0.88
Electrical	Power Supply	V, Hz	220~240 V, 50 Hz	220~240 V, 50 Hz	220~240 V, 50 Hz	220~240 V, 50 Hz
	Power Input Cooling	kW	0.16/0.57/0.75	0.17/0.93/1.05	0.32/1.39/2.18	0.3/1.95/2.6
	Heating		0.14/0.76/1.40	0.14/1.07/1.56	0.27/1.7/2.5	0.27/2.35/3.2
	Current Input Cooling	Α -	1.2/3.4/3.8	1.3/4.5/5.0	2.0/6.4/10.0	2.0/8.8 /11.5
	Heating		1.0/3.7/6.1	1.0/5.1/6.8	1.7/7.8/1.15	1.7/10.5/14.0
	Interconnecting Communication Cable	mm²	Scree	ned 0.75-1.5mm <sup>2</sup> , 2 Core, F1 F2 Conn	ection	

<sup>&</sup>lt;sup>1</sup> Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

	Accessories	
Premium Wired Controller	Sub PCB to Connect Wired Remote Controller	Central Control Network
MWR-WG00JN	MIM-A00N	MWR-R10N